

| Model | | B2320 | B2920 |
|--|---------------|---|--------------|
| Engine | | | |
| Type | | E-TVCS, liquid cooled, 3-cylinder diesel | |
| Make, Model | | Kubota D1005 | Kubota D1305 |
| PTO horsepower | HP (kW) | 17.0 (12.7) | 21.0 (15.7) |
| Engine gross horsepower | HP (kW) | 23.0 (17.2) | 29.0 (21.6) |
| Rated RPM | rpm | | |
| Bore and stroke | mm | 76 × 73.6 | 78 × 88 |
| Displacement | cc | 1001 | 1261 |
| Air cleaner | | Dual paper element | |
| Lubrication | | Forced lubrication | |
| Cooling system | | Pressurised radiator | |
| Radiator fan | | Radial air flow | |
| Capacities | | | |
| Fuel tank | ℓ | | 25 |
| Cooling system | ℓ | | 4.4 |
| Engine oil | ℓ | | 3.0 |
| Transmission case | ℓ | | 15 |
| Drive train | | | |
| Clutch | | Dry single plate | |
| Transmission | | HST (3 range) | |
| Differential lock | | Standard | |
| Final drive | | Spur gear | |
| Brake | | Multi-plate wet disc | |
| PTO | | Transmission driven with one way clutch / HSD: Live | |
| Rear | rpm | | 540, 960 |
| Mid | rpm | | 2500 |
| Hydraulics | | | |
| Type | | Open centre | |
| Pump | | Dual pump | |
| Total pump output | ℓ/min | | 31.4 |
| Hydraulic outlet | | Front outlet (w/ standard valve) | |
| 3-point hitch | | Category I | |
| Hydraulic control system | | Quarter inching valve | |
| Lift capacity | at lift point | kg | 615 |
| | 24" behind LP | kg | 480 |
| Steering | | Power steering | |
| Standard tyre size | | | |
| Front | | 6-12 | 7-12 |
| Rear | | 9.5-16 | 11.2-16 |
| Travelling speeds (at rated engine rpm) | | | |
| Forward | km/h | 0-18.9 | 0-20.2 |
| Reverse | km/h | 0-15.2 | 0-16.2 |
| Dimensions | | | |
| Overall length (w/o 3P) | mm | 2385 | 2415 |
| Overall width (min. tread) | mm | 1145 | 1245 |
| Wheelbase | mm | | 1563 |
| Ground clearance | mm | 305 | 325 |
| Turning radius with brake | m | | 2.1 |
| Weight | kg | 670 | 705 |

MID-MOUNT MOWER

| Model | | RCK54-29B | RCK60-29B |
|------------------------------|----|----------------|-----------|
| Type | | Side discharge | |
| Number of blades | | 3 | |
| Blade length | mm | 475 | 523 |
| Mounting method | | Suspended | |
| Cutting width | mm | 1372 | 1524 |
| Cutting height | mm | 25 to 127 | |
| Adjustment of cutting height | | Dial | |
| Weight (approx.) | kg | 140 | 146 |