

Specifications

Model		L3400				L4400			
		Gear-Drive Transmission		HST		Gear-Drive Transmission		HST	
		4WD		4WD		4WD		4WD	
Engine									
Type		Vertical liquid-cooled 4-cycle diesel, Indirect injection (E-TVCS)							
Engine gross power	HP (kW)	35.7 (26.6)@2700 rpm				45.3 (33.8)@2600 rpm			
Engine net power	HP (kW)	34.2 (25.5)@2700 rpm				43.0 (32.1)@2600 rpm			
PTO power	HP (kW)	30.0 (22.4)@2700 rpm		28.5 (21.3)@2700 rpm		37.5 (28.0)@2600 rpm		36.0 (26.8)@2600 rpm	
No. of cylinders		3				4			
Bore & stroke	mm	87×102.4				87×92.4			
Total displacement	cm ³	1826				2197			
Battery		12V, RC:123 min, CCA:490A				12V, RC:133 min, CCA:582A			
Fuel tank capacity	ℓ	34				42			
PTO									
Rear PTO (540 rpm)		Live-continuous running		Live-continuous with overrunning clutch		Live-independent, hydraulic PTO with PTO brake, wet clutch*			
Hydraulic									
Pump capacity (main)		ℓ/min.				23.9			
		(PS) ℓ/min.				14.5			
3-point hitch		Category I							
Lift control type		Position control							
Lift capacity at lift point		kg				906			
		at 24 in behind LP				kg			
		651				1053			
Travelling System									
Transmission		Sliding gear and constant mesh, 8 forward and 4 reverse		Hydrostatic transmission, 3 range speed		Sliding gear and constant mesh, 8 forward and 4 reverse		Hydrostatic transmission, 3 range speed	
Steering		Integral type power steering				Hydrostatic power steering			
Brakes		Wet disc type							
Clutch		Dry-type dual stage		Dry-type single stage		Dry-type single stage			
Rear differential lock		Standard							
Tyre Size		AG Standard				Front/Rear			
		7-16/11.2-24				8-16/14.9-24			
		TURF Option				Front/Rear			
		212/80-D15, 355/80-D20				27-10.5 LL15, 44×18-20			
		INDUST. Option				Front/Rear			
		27×8.50-15/15-19.5 R4				10.0-16.5/17.5-24			
Travelling Speeds w/Standard AG Tyres (at Rated Engine Speed)		Forward		Reverse		For 0-22.7		For 0-25.4	
		1.7-21.2		2.4-7.6		Rev 0-20.5		Rev 2.4-8.2	
Dimensions									
Overall length (w/o 3P)		mm				2705			
Overall width (min. tread)		mm				1305			
Overall height (w/ROPS)		mm				2160			
Wheelbase		mm				1610			
Min. ground clearance (Front axle)		mm				340			
Tread (STD Tyres)									
		Front				mm			
		1095				1155			
		Rear				mm			
		1020, 1115, 1195, 1290				1180, 1200, 1300, 1450, 1545			
Min. Turning Radius (w/brake)		m				2.5			
Weight (with ROPS)		kg		1170		1180		1430	
								1500	