

Specifications

Model		ZG222	ZG227	ZG327
		ZG222-48	ZG227-54	ZG327P-60
Engine	Model	Kubota KGZ770-E2-M3	Kubota KGZ770-E2-M2	Kubota KGZ770-E2-M1
	Type	Petrol, air-cooled V-Twin with heavy-duty canister air filter		
	Max. horsepower (Gross)	22HP@3600 rpm	27HP@3600 rpm	
	Total displacement	768 cc		
	Starting system	Key switch		
Dimensions	Overall length	2060 mm		2225 mm
	Overall width	(w/ mower)	1550 mm	1705 mm
		(w/o mower)	1220 mm	1460 mm
	Overall height	(w/ ROPS upright)	1775 mm	1915 mm
(w/ ROPS folded)		1320 mm		1555 mm
Wheel base	1295 mm		1410 mm	
Tread	Front	860 mm		975 mm
	Rear	930 mm		1150 mm
Tyre size	Front	13 × 5.0-6 Pneumatic		15 × 6.0-6 Semi-Pneumatic
	Rear	23 × 10.5-12		26 × 12.0-12
Weight (w/ mower) (without fuel)	526 kg		536 kg	670 kg
Transmission system	2-HST w/ Gear reduction			
Speed control	2-hand lever			
Travel speed range	Forward	0-14.5 km/h		0-17.0 km/h
	Reverse	0-8.0 km/h		0-8.5 km/h
Brake type	Wet multi disks, foot operated			
PTO	Type	Shaft drive		
	Clutch type	Hydraulic independent PTO clutch		
	PTO brake	Wet single disk		
Mower deck	Model	RCK48P-222Z	RCK54P-227Z	RCK60P-327Z
	Mower lift system	Hydraulic		
	Mower deck type	Pro commercial— Fabricated deck		
	Deck depth	6.0 in. (152 mm)		6.5 in. (165 mm)
	Belt type	Multi-Belt		
	Deck steel thickness	3.8 mm	4.2 mm	
	Anti-scalp roller	Rigid		
	Cutting width of mower	48 in.	54 in.	60 in.
	Number of blades	3 blades		
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments		
	Mounting system of mower	Parallel linkage		
	Blade tip speed (max.)	17000 FPM	17100 FPM	18100 FPM
Engine stop system	Key stop			
Fuel tank capacity	28 ltrs.		49 ltrs.	
Battery	12 Volts, UIL-9, 300CCA@0°F, 30 min. RC.			
Alternator capacity	14 Amps			
Hour meter	Standard			
Fuel gauge	Electric			