

Models	5065M	5075M	5085M	5095M	5105M
Rated Engine HP (ISO) 97/68/EC	65 (48 kW)	75 (56 kW)	85 (63 kW)	95 (71 kW)	105 (78 kW)
at Engine RPM	2,200	2,200	2,200	2,200	2,100
PTO HP	50 (37.3 kW)	60 (44.7 kW)	70 (52.2 kW)	80 (59.7 kW)	90 (67.1 kW)
at Rated Speed, RPM	2,100	2,100	2,100	2,100	2,100
Configurations Available <i>Key: Standard = ● Option = ■</i>					
2wd	●	●	●	●	---
MFWD	■	■	■	■	●
Open Station	●	●	●	●	■
Deluxe Open Station	■	■	■	■	●
Cab	■	■	■	■	■
Deluxe Cab	■	■	■	■	■
Engine					
Make	PowerTech 5030	PowerTech 5030	PowerTech M 4045	PowerTech M 4045	PowerTech E 4045
Aspiration	Turbocharged/Air-to-Air Aftercooled – All Models				
Cylinders	5	5	4	4	4
Displacement, cu. in/L	186/3.0	186/3.0	276/4.5	276/4.5	276/4.5
Cylinder Liners	---	---	Wet sleeved	Wet sleeved	Wet sleeved
Transmission					
Base Equipment	16F/16R SyncReverser	16F/16R SyncReverser	16F/16R SyncReverser	16F/16R SyncReverser	16F/16R PowrReverser
Optional transmissions	12F/4R SyncShuttle Plus 16F/16R PowrReverser 32F/16R PowrReverser Plus	12F/4R SyncShuttle Plus 16F/16R PowrReverser 32F/16R PowrReverser Plus	12F/4R SyncShuttle Plus 16F/16R PowrReverser 32F/16R PowrReverser Plus	12F/4R SyncShuttle Plus 16F/16R PowrReverser 32F/16R PowrReverser Plus	12F/4R SyncShuttle Plus 16F/16R SyncReverser 32F/16R PowrReverser Plus
Fuel tank capacity, standard.					
Open/Cab, (opt), [Liters]	21/30 (30/38) [80/114 (114/144)]	21/30 (30/38) [80/114 (114/144)]	29/38 [110/144]	29/38 [110/144]	29/38 [110/144]
PTO					
Standard	Independent 540/540E	Independent 540/540E	Independent 540/540E	Independent 540/540E	Independent 540/540E
Optional	540/540E/1000	540/540E/1000	540/540E/1000	540/540E/1000	540/540E/1000
PTO Actuation	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Hydraulics					
Type	Open center	Open center	Open center	Open center	Open center
Steering GPM	6.3	6.3	6.3	6.3	6.3
Implement GPM	13.2	13.2	18.4	18.4	18.4
Total GPM, Rated Output	19.4	19.4	24.7	24.7	24.7

Models	5065M	5075M	5085M	5095M	5105M
Traction Clutch					
	Wet	Wet	Wet	Wet	Wet
Final Drive					
Type	Inboard Planetary	Inboard Planetary	Inboard Planetary	Inboard Planetary	Inboard Planetary
Differential Controls	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Engage on the go rear differential lock	Yes	Yes	Yes	Yes	Yes
3 PT Hitch					
Hitch Lift Capacity, OECD/24" behind lift point, std lbs/kgs (opt lbs/kgs)	3,595/1631 (4,498/2041)	3,595/1631 (4,498/2041)	3,595/1631 (4,498/2041)	3,595/1631 (4,498/2041)	4,498/2041
Hitch Category	2, convertible to 1	2, convertible to 1	2, convertible to 1	2, convertible to 1	2, convertible to 1
Draft Sensing Type	Lower-link draft sensing	Lower-link draft sensing	Lower-link draft sensing	Lower-link draft sensing	Lower-link draft sensing
Standard Tires					
Front, 2WD (MFWD)	7.5-16 6PR F2 (11.2-24 8PR R1)	7.5-16 6PR F2 (11.2-24 8PR R1)	7.5-16 6PR F2 (11.2-24 8PR R1)	11L-15 8PR F2 (12.4R24 R1)	(12.4R24 R1)
Rear, 2WD (MFWD)	16.9-30 6PR R1 (16.9-30 6PR R1)	16.9-30 6PR R1 (16.9-30 6PR R1)	16.9-30 6PR R1 (16.9-30 6PR R1)	480/80R30 R1W (480/80R30 R1W)	(480/80R30 R1W)
Dimensions					
Wheelbase, 2WD/MFWD, in./cm	85.6/217.4	85.6/217.4	85.6/217.4	85.6/217.4	85.6/217.4
Length, including draft links, in./cm	150/381	150/381	150/381	150/381	150/381
Height, ground to top of Cab/ROPS, in./cm	99.6/96.5, 253/245.1	99.6/96.5, 253/245.1	99.6/96.5, 253/245.1	100.4/97, 255/246	100.4/97, 255/246
Weight <i>Approx. Ship Weight (less weights)</i>					
2WD Standard Open Station, lbs/kg	6,017/2729	6,017/2729	6,393/2900	6,591/2990	---
2WD Deluxe Open Station, lbs/kg	6,300/2858	6,300/2858	6,850/3107	7,000/3175	---
2WD CAB, lbs/kg	7,400/3357	7,400/3357	7,600/3447	7,750/3515	---
MFWD Standard Open Station, lbs/kg	6,400/2903	6,400/2903	6,800/3084	7,000/3175	7,300/3311
MFWD Deluxe Open Station, lbs/kg	6,700/3039	6,700/3039	7,250/3289	7,400/3357	7,700/3493
MFWD CAB, lbs/kg	7,800/3538	7,800/3538	8,000/3629	8,150/3697	8,400/3810