



GXV630

Raising the bar. On everything. The GXV630 Honda V-twin engines offer high horsepower, improved adaptability, quiet operation, and great fuel efficiency, as well as a 3 year warranty.

INTRODUCTION

COMMON APPLICATIONS

The Honda GXV630 is a beast, used throughout Australia to power commercial lawn and garden equipment, including Ride-on lawn mowers.

As well as this, the GXV630 is often used to power Construction/Industrial Equipment, as well as heavy-duty Agricultural equipment.

To see how it compares to the rest of the GXV range - and all other Honda engines - click on the "Compare Products" icon in the top right of this page

FUEL EFFICIENT OPERATION

With the simplicity of carburetion, the GXV630's fuel economy is similar to fuel injection.

It incorporates digital CDI ignition system with variable timing, insert style rod bearings and a rev limiter to protect against damage from over-revving.

A two barrel inner-vent carburetor provides more precise fuel metering, and a hemispherical combustion chamber devliers rapid combustion when you need it.

EXCEPTIONALLY QUIET

A high capacity 36 blade cooling fan and aluminium push rods with steel tips result in a lightweight, low vibration and quiet operation.

The GXV630's automatic mechanical de-compression system combines with variable ignition timing to share Honda's 'start first time, every time' reliability.

An integrated cylinder & head and racing inspired forged steel connecting rods deliver some of the smoothest performance available in an engine of this size.

3 YEAR WARRANTY

Don't forget, all Honda GXV Engines are covered by a Honda 3 Year Domestic & Commercial Warranty.

The GXV630's simple operation is renowned, but if you need assistance or spare parts, Honda's got you covered.

With over 400 authorised Honda dealers around Australia, you'll never be on your own with a Honda engine.

HIGH OUTPUT PERFORMANCE

Pressure fed crankshaft bearings

PROVEN RELIABILITY

High capacity pump facilitates consistent oil delivery

Dual panel type air filter

Large diameter air intake for superior cooling

Oil Alert

EASY TO USE AND MAINTAIN

Hour meter standard

Conveniently located controls

Automotive-type spin-on oil filter

EMISSIONS COMPLIANT

Applicable models meet the strictest world standards, contact Honda for more info

No catalyst necessary

AVAILABLE OPTIONS

High capacity charging system

Hour meter

SPECS

SPECIFICATIONS

MODEL	GXV630
TYPE	Air-cooled 4-stroke OHV petrol engine, 90° V-twin design, vertical shaft
BORE & STROKE	2 / 78 x 72 mm
DISPLACEMENT	688 cm ³
COMPRESSION RATIO	9.3:1
NET POWER	15.5 kW (20.8 HP) / 3 600 rpm
CONTINUOUS RATED POWER	10.5 kW (14.1 HP) / 3 000 rpm
MAXIMUM NET TORQUE	48.3 Nm / 4.93 kgfm / 2 500 rpm
IGNITION SYSTEM	Digital CDI with variable ignition timing
STARTING SYSTEM	Electric Start
COOLING SYSTEM	Forced-Air
FUEL CONSUMPTION AT RATED POWER	5.0 L/h at 3,600 rpm
RECOMMENDED FUEL	Unleaded

LUBRICATION SYSTEM	Full-pressure
OIL CAPACITY	2.2l
DIMENSIONS	449 x 420 x 475 mm
DRY WEIGHT	46.5kg
RRP	Please contact your local Honda dealer for a great deal. http://dl.hondampe.com.au/

VISIT HONDA POWER EQUIPMENT WEBSITE

For terms and conditions please visit http://about.hondampe.com.au/Terms_and_Conditions
The information in this document is valid as of 31/08/2015. For the most up to date information please visit <http://powerequipment.honda.com.au>